

Fireworld CO2 Fire extinguishers

Fire Extinguisher	CO2	CO2	CO2
CO2 Fire Extinguishers (Carbon dioxide)	Carbon Dioxide fire extinguishers are recommended for Class 'E' electrical hazard fires, but also have limited capabilities for extinguishing small, indoor Class 'A' paper and Class 'B' flammable liquid fires.		
Size (Capacity)	2.0KG	3.5KG	5.0KG
Part Number	FW2CO2	FW3.5CO2	FW5.0CO2
Tare Weight	5.2KG	9.2KG	12.4KG
Fire Rating	2B:E	5B:E	5B:E
Aust Standard Approval	AS/NZ 1841-2	AS/NZ 1841-2	AS/NZ 1841-2
SAI Licence Number	1511-LM-2401	1511-LM-2401	1511-LM-2401
Dimensions: Height	550mm	600mm	565mm
Dimensions: Width	110mm	140mm	150mm
Discharge time	11 seconds	14.5 seconds	20 seconds
Effective Range	1-1.5 metres	1- 2.5 metres	2-1.5 metres
Operating Pressure	1035 KPA	1345 KPA	1345 KPA
Propellant	CO2 (CARBON DIOXIDE)	CO2 (CARBON DIOXIDE)	CO2 (CARBON DIOXIDE)
Periodic Pressure Test			
:Normal Conditions	5 Years	5 Years	5 Years
:Aggressive Environment	3 Years	3 Years	3 Years
Materials : Valve	Nickel Plated Brass	Nickel Plated Brass	Nickel Plated Brass
: Cylinder	Aluminium.	Aluminium.	Aluminium.
: Cylinder Finish	Red Coated	Red Coated	Red Coated